6EM7

Dual Triode

With High-Mu Unit and Low-Mu Unit

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	6.3 ± 10%	volts
Current at 6.3 volts	0.925	amp

Direct Interelectrode Capacitances (Approx.):▲

	Unit No.1	*Unit No.2*	
Grid to plate	4.8	10	μμf
Grid to cathode and heater	2.2	7	μμf
Plate to cathode and heater	0.6	1.8	μμf


Characteristics, Class A_1 Amplifier:

	Unit No.1	*Unit No.2*	
Plate Voltage	250	150	volts
Grid Voltage	-3	-20	volts
Amplification Factor	68	5.4	
Plate Resistance (Approx.)	40000	750	ohms
Transconductance	1600	7200	μmhos
Plate Current	1.4	50	ma
Plate Current for plate volts = 60 and grid volts = 0	-	95	ma
Plate Current for grid volts = -28	-	10	ma
Grid Voltage (Approx.) for plate μa = 10	-5.5	-	volts
Grid Voltage (Approx.) for plate μa = 100	-	-45	volts

Mechanical:

Operating Position	Any
Maximum Overall Length	2-7/8" ◄
Maximum Seated Length	2-5/16" ◄
Maximum Diameter	1-9/32"
Bulb	T9
Base	Short Intermediate-Shell Octal 8-Pin with External Barriers (JEDEC Group 1, B8-58)
Basing Designation for BOTTOM VIEW	8BD

Pin 1 - Grid of Unit No.2
Pin 2 - Plate of Unit No.2
Pin 3 - Cathode of Unit No.2
Pin 4 - Grid of Unit No.1



Pin 5 - Plate of Unit No.1
Pin 6 - Cathode of Unit No.1
Pin 7 - Heater
Pin 8 - Heater

◄ Indicates a change.

VERTICAL-DEFLECTION OSCILLATOR

Values are for Unit No.1

Maximum Ratings, *Design-Maximum Values:*

For operation in a 525-line, 30-frame system[b]

DC PLATE VOLTAGE	330	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE	400	max.	volts
CATHODE CURRENT:			
Peak	77	max.	ma
Average	22	max.	ma
PLATE DISSIPATION	1.5	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode	200	max.	volts
Heater positive with respect to cathode	200[c]	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:			
For grid-resistor-bias or cathode-bias operation	2.2	max.	megohms

VERTICAL-DEFLECTION AMPLIFIER

Values are for Unit No.2

Maximum Ratings, *Design-Maximum Values:*

For operation in a 525-line, 30-frame system[b]

DC PLATE VOLTAGE	330	max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE[d]	1500	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE	250	max.	volts
CATHODE CURRENT:			
Peak	175	max.	ma
Average	50	max.	ma
PLATE DISSIPATION	10	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode	200	max.	volts
Heater positive with respect to cathode	200[c]	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:			
For grid-resistor-bias or cathode-bias operation	2.2	max.	megohms

[a] Without external shield.


[b] As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.

[c] The dc component must not exceed 100 volts.

[d] This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one vertical scanning cycle. In a 525-line, 30-frame system, 15 per cent of one vertical scanning cycle is 2.5 milliseconds.


OPERATING CONSIDERATIONS

The *bulb* becomes hot during operation. To insure adequate cooling, therefore, it is essential that free circulation of air be provided.


1.188" MAX.
1.062" MIN.
DIA.
T9 BULB
2 5/16" MAX.
2 7/8" MAX.
BASE
JEDEC GROUP 1
No B8-58
1 9/32" MAX. DIA.
92CS-10880


6EM7

AVERAGE PLATE CHARACTERISTICS
Unit No.1



92CM-9912


AVERAGE CHARACTERISTICS
Unit No.1



92CM-9915RI


6EM7

AVERAGE PLATE CHARACTERISTICS
Unit No.2



92CM-10466

AVERAGE CHARACTERISTICS
Unit No. 2



92CM-10467